

AMENDMENTS IN THE CLAIMS

Please amend the claims as follows:

1. (Currently Amended) A method for disabling monitoring of an instrumentation event in a simulation hardware description language (HDL) model of a circuit design within a batch simulation farm, in which said HDL model including an instrumentation entity that detects an instrumentation event and delivers a signal to an instrumentation logic block to indicate an occurrence of an instrumentation event during simulation of said circuit design, said batch simulation farm including a simulation client communicates with in which the HDL model is simulation tested and further including an instrumentation server to process simulation data with respect to said simulation model communicatively coupled to the simulation client, said method comprising:

assembling an instrumentation event disable list within said instrumentation server, wherein said instrumentation event disable list lists instrumentation events to be disabled within said HDL simulation model; and

prior to simulating said ~~simulation~~ HDL model within said simulation client:

retrieving said instrumentation event disable list from said instrumentation server;

and

disabling monitoring of instrumentation events specified ~~within~~ by said instrumentation event disable list.

2. (Original) The method of claim 1, wherein said assembling an instrumentation event disable list comprises:

identifying an instrumentation event to be disabled during simulation processing of said simulation model; and

delivering to said instrumentation server an instrumentation event name corresponding to said instrumentation event within said instrumentation event disable list.

3. (Original) The method of claim 2, further comprising, in response to receiving said delivered instrumentation event name at said instrumentation server, adding said instrumentation

event name to a master disable file within said instrumentation server, wherein said master disable file contains a list of instrumentation events to be disabled for said simulation model.

4. (Original) The method of claim 1, wherein said simulation client includes a model simulator and a run time executive program for controlling simulation processing of said simulation model within said model simulator, said retrieving said instrumentation event disable list comprising:

issuing a request from said run time executive program to an application program interface (API) entry point within said simulator to retrieve said instrumentation event disable list;

responsive to said request to retrieve said instrumentation event disable list, attempting to access said instrumentation server; and

responsive to a successful access to said instrumentation server, delivering said master disable file to said simulation client.

5. (Original) The method of claim 4, wherein an alternate copy of said instrumentation event disable list is stored within a shared file system, said method further comprising, in response to an unsuccessful access attempt to instrumentation server, attempting to access said shared file system.

6. (Original) The method of claim 5, wherein said alternate copy is periodically updated from said master disable file.

7. (Currently Amended) A system for disabling monitoring of an instrumentation event in a simulation hardware description language (HDL) model of a circuit design within a batch simulation farm, in which said HDL model including an instrumentation entity that detects an instrumentation event and delivers a signal to an instrumentation logic block to indicate an occurrence of an instrumentation event during simulation of said circuit design, said batch simulation farm including a simulation client communicates with in which the HDL model is simulation tested and further including an instrumentation server to process simulation data with respect to said simulation model communicatively coupled to the simulation client, said system comprising:

processing means for assembling an instrumentation event disable list within said instrumentation server, wherein said instrumentation event disable list lists instrumentation events to be disabled within said HDL simulation model; and

processing means responsive to simulating said ~~simulation~~ HDL model within said simulation client for:

retrieving said instrumentation event disable list from said instrumentation server;

and

disabling monitoring of instrumentation events specified within by said instrumentation event disable list.

8. (Original) The system of claim 7, wherein said processing means for assembling an instrumentation event disable list comprises:

processing means for identifying an instrumentation event to be disabled during simulation processing of said simulation model; and

processing means for delivering to said instrumentation server an instrumentation event name corresponding to said instrumentation event within said instrumentation event disable list.

9. (Original) The system of claim 8, further comprising, processing means responsive to receiving said delivered instrumentation event name at said instrumentation server for adding said instrumentation event name to a master disable file within said instrumentation server, wherein said master disable file contains a list of instrumentation events to be disabled for said simulation model.

10. (Original) The system of claim 7, wherein said simulation client includes a model simulator and a run time executive program for controlling simulation processing of said simulation model within said model simulator, said processing means for retrieving said instrumentation event disable list comprising:

processing means for issuing a request from said run time executive program to an application program interface (API) entry point within said simulator to retrieve said instrumentation event disable list;

processing means responsive to said request to retrieve said instrumentation event disable list for attempting to access said instrumentation server; and

processing means responsive to a successful access to said instrumentation server for delivering said master disable file to said simulation client.

11. (Original) The system of claim 10, wherein an alternate copy of said instrumentation event disable list is stored within a shared file system, said system further comprising, processing means responsive to an unsuccessful access attempt to instrumentation server for attempting to access said shared file system.

12. (Original) The system of claim 11, wherein said alternate copy is periodically updated from said master disable file.

13. (Currently Amended) A computer program product for disabling monitoring of an instrumentation event in a ~~simulation~~ hardware description language (HDL) model of a circuit design within a batch simulation farm, in which said HDL model including an instrumentation entity that detects an instrumentation event and delivers a signal to an instrumentation logic block to indicate an occurrence of an instrumentation even during simulation of said circuit design, said batch simulation farm including a simulation client ~~communicates with~~ in which the HDL model is simulation tested and further including an instrumentation server to ~~process simulation data with respect to said simulation model~~ communicatively coupled to the simulation client, said computer program product comprising:

program instruction means for assembling an instrumentation event disable list within said instrumentation server, wherein said instrumentation event disable list lists instrumentation events to be disabled within said HDL simulation model; and

program instruction means responsive to simulating said ~~simulation~~ HDL model within said simulation client for:

retrieving said instrumentation event disable list from said instrumentation server;

and

disabling monitoring of instrumentation events specified within by said instrumentation event disable list.

14. (Original) The computer program product of claim 13, wherein said program instruction means for assembling an instrumentation event disable list comprises:

program instruction means for identifying an instrumentation event to be disabled during simulation processing of said simulation model; and

program instruction means for delivering to said instrumentation server an instrumentation event name corresponding to said instrumentation event within said instrumentation event disable list.

15. (Original) The computer program product of claim 14, further comprising, program instruction means responsive to receiving said delivered instrumentation event name at said instrumentation server for adding said instrumentation event name to a master disable file within

said instrumentation server, wherein said master disable file contains a list of instrumentation events to be disabled for said simulation model.

16. (Original) The computer program product of claim 13, wherein said simulation client includes a model simulator and a run time executive program for controlling simulation processing of said simulation model within said model simulator, said program instruction means for retrieving said instrumentation event disable list comprising:

program instruction means for issuing a request from said run time executive program to an application program interface (API) entry point within said simulator to retrieve said instrumentation event disable list;

program instruction means responsive to said request to retrieve said instrumentation event disable list for attempting to access said instrumentation server; and

program instruction means responsive to a successful access to said instrumentation server for delivering said master disable file to said simulation client.

17. (Original) The computer program product of claim 16, wherein an alternate copy of said instrumentation event disable list is stored within a shared file system, said computer program product further comprising, program instruction means responsive to an unsuccessful access attempt to instrumentation server for attempting to access said shared file system.

18. (Original) The computer program product of claim 17, wherein said alternate copy is periodically updated from said master disable file.

19. (New) A method for disabling monitoring of an instrumentation event in a hardware description language (HDL) model of a circuit design within a batch simulation farm, said HDL model including an instrumentation entity that detects an instrumentation event and delivers a signal to an instrumentation logic block to indicate an occurrence of an instrumentation event during simulation of said circuit design, said batch simulation farm including a simulation client in which the HDL model is simulation tested and further including an instrumentation server communicatively coupled to the simulation client, said method comprising:

maintaining, within said instrumentation server, an event disable list for each active HDL model within said simulation batch farm;

including within each event disable list, a list of instrumentation events to be disabled for a corresponding HDL model; and

prior to simulating said HDL model within said simulation client:

retrieving an event disable list corresponding to said HDL model from said instrumentation server; and

disabling monitoring of instrumentation events specified by said event disable list.

20. (New) The method of claim 19, wherein said disabling comprises setting, within said instrumentation logic block, event mask registers corresponding to instrumentation events included in said event disable list.

21. (New) The method of claim 20, wherein said simulation client includes a model simulator and a run time executive program for controlling simulation processing of said simulation model within said model simulator, wherein said setting event mask registers is performed using an application program interface entry point within said model simulator.